

#### DESCRIPTIVE

- Generating set running on natural gas or LPG (natural gas supplied configuration)
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 40 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

#### POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

#### TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

#### ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

## GZ150

Engine ref.	PSI88TIC
Alternator ref.	KH01430T

#### GENERAL CHARACTERISTICS

Frequency (Hz)	50 Hz
Voltage (V)	400/230
Standard Control Panel	DEC 3000

#### POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
400/230	117	146	106	133	211

#### DIMENSIONS COMPACT VERSION

Length (mm)	2800
Width (mm)	1120
Height (mm)	1539

#### DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	
Length (mm)	3526
Width (mm)	1154
Height (mm)	1724
Dry weight (kg)	1863
Acoustic pressure level @1m in dB(A)	81
Sound power level guaranteed (Lwa)	100

#### Fuel System 50 Hz:

**Natural gas fuel supply pressure, kPa (in. H2O) :**  
**Nat. Gas : 1.74--2.74 (7-11)**

#### Fuel Composition Limits \* (Nat.Gaz):

Methane, % by volume	90 min.
Ethane, % by volume	4.0 max.
Propane, % by volume	1.0 max.
Propene, % by volume	0.1 max.
C4 and higher, % by volume	0.3 max
Sulfur, ppm mass	25 max.
Lower heating value, MJ/m3 (Btu/ft3), min :	33.2 (890)

\* Fuels with other compositions may be acceptable. If your fuel is outside the listed specifications

**Online carburation entry : 1 (<=GZ100) / 1.5 (<=GZ150) / 2 (<=GZ250) / 3 (>=GZ300) NPTF**

### GENERAL ENGINE DATA

Engine brand	PSI
Engine ref.	PSI88TIC
Air inlet system	Turbo
Cylinders configuration	V
Number of cylinders	8
Displacement (L)	8,67
Charge Air coolant	Air/Air DC
Bore (mm) x Stroke (mm)	110 x 114
Compression ratio	10.1 : 1
Speed (RPM)	1500
Pistons speed (m/s)	5,7
Maximum stand-by power at rated RPM (kW)	161
Frequency regulation, steady state (%) +/-	0.5%
BMEP (bar)	13,5
Governor type	Electronic

### COOLING SYSTEM

Radiator & Engine capacity (L)	27,6
Fan power (kW)	10,8
Fan air flow w/o restriction (m3/s)	4,3
Available restriction on air flow (mm H2O)	12,5
Type of coolant	Glycol-Ethylene

### EMISSIONS

Emission PM (g/kW.h)	
Emission CO (g/kW.h)	
Emission HC+NOx (g/kWh)	0
Emission HC (g/kW.h)	

### EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	649
Exhaust gas flow @ ESP 50 Hz (L/s)	380
Max. exhaust back pressure (mm H2O)	1000

### FUEL

Gaznat Consumption @ 110% load (m3/h)	46,4
Gaznat Consumption @ 100% load (m3/h)	43
Gaznat Consumption @ 75% load (m3/h)	34
Gaznat Consumption @ 50% load (m3/h)	24,2

### OIL

Oil capacity (L)	8,5
Min. oil pressure (bar)	
Max. oil pressure (bar)	
Oil consumption 100% ESP (L/h)	0
Oil sump capacity (L)	8

### HEAT BALANCE

Heat rejection to exhaust (kW)	
Radiated heat to ambient (kW)	19
Heat rejection to coolant HT (kW)	62,5

### AIR INTAKE

Max. intake restriction (mm H2O)	
Intake air flow (L/s)	123

### GENERAL DATA

Alternator commercial brand	KOHLER
Alternator ref.	KH01430T
Number of Phase	Three phase
Power factor (Cos Phi)	0,8
Altitude (m)	0 à 2500
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 In for 10 s	No
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class (H/163°C), standby 27°C	H / 163°K
AVR Regulation	
Total Harmonic Distortion in no-load DHT (%)	2.38
Total Harmonic Distortion, on linear load DHT (%)	2.11
Wave form : NEMA=TIF	27.6
Wave form : CEI=FHT	0.62
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	2
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 23
Technology	Without collar or brush

### OTHER DATA


Continuous Nominal Rating 40°C (kVA)	144
Standby Rating 27°C (kVA)	89,3
Efficiencies 100% of load (%)	90,1
Air flow (m3/s)	0,338
Short circuit ratio (Kcc)	0,45
Direct axis synchro reactance unsaturated (Xd) (%)	222
Quadra axis synchro reactance unsaturated (Xq) (%)	113
Open circuit time constant (T'do) (ms)	885
Direct axis transient reactance saturated (X'd) (%)	18,1
Short circuit transient time constant (T'd) (ms)	71
Direct axis subtransient reactance saturated (X''d) (%)	7,9
Subtransient time constant (T''d) (ms)	
Quadra axis subtransient reactance saturated (X''q) (%)	7,56
Subtransient time constant (T''q) (ms)	
Zero sequence reactance unsaturated (Xo) (%)	0,6
Negative sequence reactance saturated (X2) (%)	7,86
Armature time constant (Ta) (ms)	8
No load excitation current (io) (A)	
Full load excitation current (ic) (A)	
Full load excitation voltage (uc) (V)	
Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	338
Transient dip (4/4 load) - PF : 0,8 AR (%)	12,53
No load losses (W)	3770
Heat rejection (W)	13090
Unbalanced load acceptance ratio (%)	

## DIMENSIONS

### Dimensions soundproofed version

Type soundproofing	
Length (mm)	3526
Width (mm)	1154
Height (mm)	1724
Dry weight (kg)	1863
Acoustic pressure level @1m in dB(A)	81
Sound power level guaranteed (Lwa)	100

DEC3000, comprehensive and simple



Generator Controls / Decision-Maker® 3000

The Decision-Maker® 3000 generator set controller provides advanced control, system monitoring, and system diagnostics for optimum performance. The Decision-Maker® 3000 controller meets NFPA 110, Level 1 when equipped with the necessary accessories and installed per NFPA standards. The Decision-Maker® 3000 controller uses patented software logic to manage sophisticated functions, such as voltage regulation and alternator thermal overload protection, normally requiring additional hardware. Additional features include:

- A digital display and pushbutton/rotary selector al provide easy local access to data.
- Measurements selectable in metric or English units.
- Scrolling display shows critical data at a glance.
- Digital display of power metering (Kw and Kva).
- Integrated hybrid voltage regulator providing  $\pm 0.5\%$  regulation.
- Built-in alternator thermal overload protection.

