



DESCRIPTIVE

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- Exhaust compensators with flanges
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

*DCC : Data Center Continuous Power ratings apply to Data Center installations where a reliable utility power is available and comply with Uptime institute Tier III and IV requirements.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

T2200

Engine ref.	S16R-PTAA2
Alternator ref.	KH04973T
Performance class	G3

GENERAL CHARACTERISTICS

Frequency (Hz)	50 Hz
Voltage (V)	400/230
Standard Control Panel	NA
Optional control panel	M80
Optional Control Panel	APM403
Optional control panel	APM802

POWER

Voltage	ESP		PRP		DCC (*)		Standby Amps
	kW _e	kVA	kW _e	kVA	kW _e	kVA	
415/240	1804	2255	1640	2050	1640	2050	3137
400/230	1804	2255	1640	2050	1640	2050	3255
380/220	1804	2255	1640	2050	1640	2050	3426

DIMENSIONS COMPACT VERSION

Length (mm)	5595
Width (mm)	2286
Height (mm)	2563
Dry weight (kg)	14215
Tank capacity (L)	

DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	
Length (mm)	5595
Width (mm)	2286
Height (mm)	2563
Dry weight (kg)	14215
Tank capacity (L)	
Acoustic pressure level @1m in dB(A)	
Sound power level guaranteed (Lwa)	
Acoustic pressure level @7m in dB(A)	

GENERAL ENGINE DATA

Engine brand	MITSUBISHI
Engine ref.	S16R-PTAA2
Air inlet system	Turbo
Cylinders configuration	V
Number of cylinders	16
Displacement (L)	65,37
Charge Air coolant	Air/Air DC
Bore (mm) x Stroke (mm)	170 x 180
Compression ratio	13.5 : 1
Speed (RPM)	1500
Pistons speed (m/s)	9
Maximum stand-by power at rated RPM (kW)	1895
Frequency regulation, steady state (%) +/-	0.25%
BMEP at Max Power (bar)	21,1
Governor type	Electronic

COOLING SYSTEM

Radiator & Engine capacity (L)	370
Fan power (kW)	39
Fan air flow w/o restriction (m ³ /s)	33,8
Available restriction on air flow (mm H ₂ O)	20
Type of coolant	Glycol-Ethylene

EMISSIONS

Emission PM (mg/Nm ³) 5% O ₂	90
Emission CO (mg/Nm ³) 5% O ₂	550
Emission HC+NO _x (g/kWh)	14,4
Emission HC (mg/Nm ³) 5% O ₂	100

EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	524
Exhaust gas flow @ ESP 50 Hz (L/s)	7000
Max. exhaust back pressure (mm H ₂ O)	600

FUEL

Consumption @ 110% load (L/h)	458,1
Consumption @ 100% load (L/h)	401,7
Consumption @ 75% load (L/h)	307,3
Consumption @ 50% load (L/h)	212,8
Maximum fuel pump flow (L/h)	588

OIL

Oil system capacity including filters (L)	230
Min. oil pressure (bar)	2,5
Max. oil pressure (bar)	6,5
Oil consumption 100% ESP (L/h)	1,5
Oil sump capacity (L)	140

HEAT BALANCE

Heat rejection to exhaust (kW)	1443
Radiated heat to ambient (kW)	139
Heat rejection to coolant HT (kW)	

AIR INTAKE

Max. intake restriction (mm H ₂ O)	400
Intake air flow (L/s)	2650

GENERAL DATA

Alternator ref.	KH04973T
Number of Phase	Three phase
Power factor (Cos Phi)	0,8
Altitude (m)	0 à 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 In for 10 s	Yes
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class (H/163°C), standby 27°C	H / 163°K
AVR Regulation	Yes
Total Harmonic Distortion in no-load DHT (%)	<3.5
Total Harmonic Distortion, on linear load DHT (%)	<3.5
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	<2
Number of bearing	Single Bearing
Coupling	Direct
Voltage regulation at established rating (+/- %)	0,5
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 23
Technology	Brushless

OTHER DATA

Continuous Nominal Rating 40°C (kVA)	2050
Standby Rating 27°C (kVA)	2255
Efficiencies 100% of load (%)	96,1
Air flow (m3/s)	2,5
Short circuit ratio (Kcc)	0,38
Direct axis synchro reactance unsaturated (Xd) (%)	350,2
Quadra axis synchro reactance unsaturated (Xq) (%)	186,2
Open circuit time constant (T'do) (ms)	2513,68
Direct axis transient reactance saturated (X'd) (%)	27,7
Short circuit transient time constant (T'd) (ms)	228,29
Direct axis subtransient reactance saturated (X''d) (%)	14,4
Subtransient time constant (T''d) (ms)	14,376
Quadra axis subtransient reactance saturated (X''q) (%)	14,9
Subtransient time constant (T''q) (ms)	19,6
Zero sequence reactance unsaturated (Xo) (%)	2,41
Negative sequence reactance saturated (X2) (%)	14,66
Armature time constant (Ta) (ms)	28,843
No load excitation current (io) (A)	1,21
Full load excitation current (ic) (A)	4,17
Full load excitation voltage (uc) (V)	44,1
Engine start (Delta U = 20% perm. or 30% trans.) (kVA)	1827,57
Transient dip (4/4 load) - PF : 0,8 AR (%)	19,31
No load losses (W)	17333,0
Heat rejection (W)	1
	66408,0
	5
Unbalanced load acceptance ratio (%)	8

DIMENSIONS

Contener dimensions ISO40 version

Type soundproofing	ISO40 Si
Length (mm)	12192
Width (mm)	2438
Height (mm)	2896
Dry weight (kg)	23090
Tank capacity (L)	500
Acoustic pressure level @1m in dB(A)	93
Sound power level guaranteed (Lwa)	116
Acoustic pressure level @7m in dB(A)	85

Basic terminal block



The control unit can be used as a basic terminal block for connecting a control box.

Offers the following functions:

emergency stop button, customer connection terminal block, CE.

M80, transfer of information




The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE.

APM403, basic generating set and power plant control



The APM403 is a versatile control unit which allows operation in manual or automatic mode
 Measurements : voltage and current
 kW/kWh/kVA power meters
 Standard specifications: Voltmeter, Frequency meter.
 Optional : Battery ammeter.
 J1939 CAN ECU engine control
 Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
 Engine parameters: Fuel level, hour counter, battery voltage.
 Optional (standard at 24V): Oil pressure, water temperature.
 Event log/ Management of the last 300 genset events.
 Mains and genset protection
 Clock management
 USB connections, USB Host and PC,
 Communications : RS485 INTERFACE
 ModBUS protocol /SNMP
 Optional : Ethernet, GPRS, remote control, 3G, 4G,
 Websupervisor, SMS, E-mails

APM802 dedicated to power plant management



The new APM802 command/control system is specifically designed for operating and monitoring power plants for markets including hospitals, data centres, banks, the oil and gas sector, industries, IPP, rental and mining.
 This unit is available as standard on all generating sets from 275 Kva designed for coupling. It is optional on the rest of our range.

The Human Machine Interface, designed in collaboration with a company specialising in interface design, facilitates operations with a large 100% touch screen. The pre-configured system for power plant applications features a brand new customisation function which complies with the international standard IEC 61131-3. New communication functions (PLC and regulation), improve the high level of equipment availability in the installation.

Advantages:
 Dedicated to power plant management.
 Specially researched ergonomics.
 High level of equipment availability.
 Modularity and long service life guaranteed.
 Making it easy to extend the installation

For more information, please refer to the sales documentation.