



#### DESCRIPTIVE

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

#### POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

#### TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

#### ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.



## T12HK

Engine ref.	L3E-SDH
Alternator ref.	AT00361T
Performance class	G2

#### GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	APM303
Optional control panel	TELYS
Optional Control Panel	Basic terminal block

#### POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
230 TRI	9,6	12	-	-	30
400/230	9,6	12	-	-	17

#### DIMENSIONS COMPACT VERSION

Length (mm)	1220
Width (mm)	700
Height (mm)	922
Dry weight (kg)	260
Tank capacity (L)	50

#### DIMENSIONS SOUNDPROOFED VERSION

Commercial reference of the enclosure	M125
Length (mm)	1482
Width (mm)	760
Height (mm)	1030
Dry weight (kg)	380
Tank capacity (L)	50
Acoustic pressure level @1m in dB(A)	80
Sound power level guaranteed (Lwa)	95
Acoustic pressure level @7m in dB(A)	66

## T12HK

### ENGINE CHARACTERISTICS

## GENERAL ENGINE DATA

Engine brand	MITSUBISHI
Engine ref.	L3E-SDH
Air inlet system	Athmo
Cylinders configuration	L
Number of cylinders	3
Displacement (L)	0,95
Charge Air coolant	
Bore (mm) x Stroke (mm)	76,00 x 70,00
Compression ratio	23 : 1
Speed (RPM)	3000
Pistons speed (m/s)	7,00
Maximum stand-by power at rated RPM (kW)	16,40
Frequency regulation, steady state (%) +/- 2.5%	
BMEP (bar)	6,00
Governor type	Mechanical

## COOLING SYSTEM

Radiator & Engine capacity (L)	3,70
Max water temperature (°C)	111,00
Outlet water temperature (°C)	93
Fan power (kW)	1,80
Fan air flow w/o restriction (m3/s)	0,90
Available restriction on air flow (mm H2O)	10,00
Type of coolant	Glycol-Ethylene
Thermostat modulating range HT (°C)	76.5-90

## EMISSIONS

Emission PM (mg/Nm3) 5% O2	100
Emission CO (mg/Nm3) 5% O2	250
Emission HC+NOx (g/kWh)	
Emission HC (mg/Nm3) 5% O2	20

## EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	590
Exhaust gas flow @ ESP 50 Hz (L/s)	54,30
Max. exhaust back pressure (mm H2O)	800

## FUEL

Consumption @ 110% load (L/h)	
Consumption @ 100% load (L/h)	5,10
Consumption @ 75% load (L/h)	4,20
Consumption @ 50% load (L/h)	3,20
Maximum fuel pump flow (L/h)	18,00

## OIL

Oil capacity (L)	4,10
Min. oil pressure (bar)	0,50
Max. oil pressure (bar)	4,00
Oil consumption 100% load (L/h)	0,014
Oil sump capacity (L)	3,6

## HEAT BALANCE

Heat rejection to exhaust (kW)	15
Radiated heat to ambient (kW)	2,00
Heat rejection to coolant (kW)	18.6

## AIR INTAKE

Max. intake restriction (mm H2O)	310
Intake air flow (L/s)	19,70



# T12HK

## ALTERNATOR CHARACTERISTICS

### GENERAL DATA

Alternator ref.	AT00361T
Number of Phase	Three phase
Power factor (Cos Phi)	0,8
Altitude (m)	0 to 1000
Overspeed (rpm)	0
Number of pole	2
Capacity for maintaining short circuit at 3 In for 10 s	No
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class, standby 27°C	H / 163°K
%regulation_avr%	#regulation_avr#
Total Harmonic Distortion in no-load DHT (%)	Ôěň4
Total Harmonic Distortion, on load DHT (%)	Ôěň4
Wave form : NEMA=TIF	
Wave form : CEI=FHT	
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	
Recovery time (Delta U = 20% transient) (ms)	
Indication of protection	IP 23
Technology	Collar and brush
AVR Regulation	No

### OTHER DATA

Continuous Nominal Rating 40°C (kVA)	16,0
Standby Rating 27°C (kVA)	
Efficiencies 100% of load (%)	84,5
Air flow (m3/s)	0,000
Short circuit ratio (Kcc)	
Direct axis synchro reactance unsaturated (Xd) (%)	
Quadra axis synchro reactance unsaturated (Xq) (%)	
Open circuit time constant (T'do) (ms)	
Direct axis transient reactance saturated (X'd) (%)	
Short circuit transient time constant (T'd) (ms)	
Direct axis subtransient reactance saturated (X''d) (%)	
Subtransient time constant (T''d) (ms)	
Quadra axis subtransient reactance saturated (X''q) (%)	
Subtransient time constant (T''q) (ms)	
Zero sequence reactance unsaturated (Xo) (%)	
Negative sequence reactance saturated (X2) (%)	
Armature time constant (Ta) (ms)	
No load excitation current (io) (A)	0,90
Full load excitation current (ic) (A)	
Full load excitation voltage (uc) (V)	90,0
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	
Transient dip (4/4 load) - PF : 0,8 AR (%)	
No load losses (W)	
Heat rejection (W)	
Unbalanced load acceptance ratio (%)	

### APM303, comprehensive and simple



The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

**Measurements:**  
 phase-to-neutral and phase-to-phase voltages, fuel level  
 (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)

**Supervision:**  
 Modbus RTU communication on RS485

**Reports:**  
 (In option : 2 configurable reports)

**Safety features:**  
 Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)

**Traceability:**  
 Stack of 12 stored events

For further information, please refer to the data sheet for the APM303.

### TELYS, ergonomic and user-friendly



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

**Electrical measurements:** voltmeter, frequency meter, ammeter.

**Engine parameters:** working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

**Alarms and faults:** oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

**Ergonomics:** wheel for navigating around the various menus.

**Communication:** remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

## Basic terminal block



The control unit can be used as a basic terminal block for connecting a control box.

Offers the following functions:

emergency stop button, customer connection terminal block, CE.